



INSTRUMENTATION VALVES

Blue Ribbon Corporation's High-quality instrumentation valves are designed for heavy-duty process control or other industrial applications that require high-pressure carbon steel or stainless steel shut-off valves.

Our valves are available hard seat (10,000 PSI) or soft seat (6,000 PSI), 1/4" or 1/2" NPT, straight or angle pattern, male x male, female x female, or male x female configurations to suit a variety of requirements.

NVS Super Mini			NV (1/4" NPT) Mini			NV (1/2" NPT) & NVL (1/4" NPT) Full Size			HV Hex Body			GV Multi-Port		
	In.	mm		In.	mm		In.	mm		In.	mm		In.	mm
A	1.02	26	A	1.81	46	A	2.67	68	A	3.65	93	A	3.68	93
B	0.32	8	B	0.50	13	B	2.64	67	B	3.23	82	B	4.46	113
C1	0.40	10	C	0.17	4	C	1.12	29	C	1.26	32	C	1.26	32
C2	0.20	6	D	0.44	11	D	0.73	19	D	1.65	42	D	1.61	41
D	0.46	12	E	0.34	9	E	2.25	57	E	0.75	19	E	0.82	21
E	0.75	19	F	0.75	19				F	2.25	57	F	2.25	57
F	0.52	13	G	0.61	15									
G	1.31	33	H	1.04	26									

Part Number System:

<p>Valve Designation</p> <p>NVS = "Super Mini" Style NV = Standard Size NVL = Full Size Body 1/4" NPT HV = Hex Body Valve GV = Multi-Port Gauge Valve</p> <p>Body Material</p> <p>CS = Carbon Steel SS = 316 Stainless Steel</p> <p>Connection Size</p> <p>1/4 = 1/4" NPT 3/8 = 3/8" NPT 1/2 = 1/2" NPT</p>	<p>Outlet Connection</p> <p>F = Female M = Male</p> <p>Inlet Connection</p> <p>F = Female M = Male</p> <p>Body Pattern</p> <p>180 = Straight Pattern 90 = Angle Pattern</p> <p>Seat / Pressure Rating</p> <p>GS = Gas Service / 6000 PSI HS = Hydraulic Service / 1000 PSI</p>
---	--

